TECHNICAL DATA SHEET

# PROTECT 700

ANTIADESIVO SENZA SILICONE PER LA SALDATURA AUTOMATICA




## CARATTERISTICHE

| | |
|---|---|
| Base: | fluidi distaccanti. |
| Biodegradabilità: | sup. al 80% |
| Aspetto: | fluido trasparente giallino |
| Viscosità a 25°C (Brookfield): | 20-50 cSt |
| Odore: | inodore |
| Resistenza a temperatura: | ottima |

**Contiene materia prima di origine vegetale e rinnovabile**.

## CAMPI D'IMPIEGO

Carpenterie metalliche: in tutti i casi di saldatura a filo, a elettrodo e automatica.

## ISTRUZIONI D'IMPIEGO

Vaporizzare con aria compressa o stendere il prodotto con un pennello sulle superfici da trattare o sulle torce da saldatura.
Il prodotto può essere utilizzato puro o diluito con acqua sino al 50%.
Per diluire il prodotto aggiungere acqua mescolando il prodotto.
Può essere utilizzato anche sugli impianti autogeni per la saldatura predisposti con un sistema di distribuzione automatica del prodotto.
Per successivi trattamenti di verniciatura si consiglia di pulire la superficie da trattare con appositi detergenti per metalli.

## CONFEZIONI

Fusti da 5-25-50-200 kg
Codice 10650/50

Data ultima revisione: 07/11/2023

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.
® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.



**Siliconi Commerciale® SpA**
Via Francia 4, 36053 Gambellara (VI) ITALY
**Tel:** +39 0444 649766
**Fax:** +39 0444 440018
**email:** info@siliconi.it
**www.siliconi.it**